

RANGE COMPOSITION

EVO900: a range designed to guarantee the highest level of performance, reliability, energy saving, safety standards and ergonomic operation. These concepts are reflected throughout the line in its modularity, construction and numerous configurations: countertop (on base or table), free-standing, on concrete or stainless steel plinth, bridged or cantilever. Thanks to its advanced technology and premium performance, EVO900 is a perfect solution for restaurants as well as large institutions needing high power and high productivity. The models detailed in this sheet are 4 electric boiling tops with 2 or 4 hot plates.



EVO900

ELECTRIC BOILING TOPS **ZANUSSI** PROFESSIONAL



FUNCTIONAL AND CONSTRUCTION FEATURES

- ◆ The electric boiling top range is ideal for kitchens needing a flexible, powerful and easy to clean cooking top.
- ◆ Cast-iron hot plates hermetically sealed to the one-piece top, with safety thermostat.
- ◆ Hot plates with a power of 4 kW.
- ◆ Worktop in 20/10 stainless steel.



- Front and side panels in stainless steel with Scotch Brite finish.
- ◆ All models have right-angled side edges to allow flush-fitting joins between units, eliminating gaps and possible dirt traps.
- ◆ The special design of the control knob system guarantees against water infiltration.
- ◆ Main connections can be via the bottom of the unit.
- ◆ Access to all components from the front.
- ◆ All models can be easily mounted

- on open base cupboards, bridging supports or cantilever system.
- ◆ IPX5 water protection.

TECHNICAL DATA				
CHARACTERISTICS	MODELS			
	Z9ECED2Q00 392039	Z9ECEH4Q00 392040	Z9ECED2Q0N 392165	Z9ECEH4Q0N 392166
Power supply	Electric	Electric	Electric	Electric
External dimensions - mm				
width	400	800	400	800
depth	900	900	900	900
height	250	250	250	250
Back plate dimensions - mm	300x300	300x300, 300x300	300x300	300x300, 300x300
Back plates power - kW	4	4, 4	4	4, 4
Front plates dimension - mm	300x300	300x300, 300x300	300x300	300x300, 300x300
Front plates power - kW	4	4, 4	4	4, 4
Total Power - kW	8	16	8	16
Net weight - kg.	35	69	35	69
Supply voltage	400 V, 3N, 50/60	400 V, 3N, 50/60	230 V, 3, 50/60	230 V, 3, 50/60



597858N00



597858R00

LEGEND

	Z9ECED2Q00 392039	Z9ECEH4Q00 392040	Z9ECED2Q0N 392165	Z9ECEH4Q0N 392166
EI - Electrical connection	400 V, 3N, 50/60	400 V, 3N, 50/60	230 V, 3, 50/60	230 V, 3, 50/60

OPTIONAL ACCESSORIES

ACCESSORIES	MODELS			
	Z9ECED2Q00 392039	Z9ECEH4Q00 392040	Z9ECED2Q0N 392165	Z9ECEH4Q0N 392166
2 CAST IRON PLATE BARS FOR EL.COOK.TOP	206056	206056	206056	206056
2 SIDE COVERING PANELS H=250-D=900-Z/OEM	206321	206321	206321	206321
CHIMNEY UPSTAND 400MM	206303		206303	
CHIMNEY UPSTAND 800MM		206304		206304
FRONTAL HANDRAIL 1200 MM	206191	206191	206191	206191
FRONTAL HANDRAIL 1600 MM	206192	206192	206192	206192
FRONTAL HANDRAIL 400 MM	206166		206166	
FRONTAL HANDRAIL 800 MM	206167	206167	206167	206167
JUNCTION SEALING KIT	206086	206086	206086	206086
LARGE HANDRAIL(PORIONING SHELF)400 MM	206185	206185	206185	206185
LARGE HANDRAIL(PORIONING SHELF)800 MM	206186	206186	206186	206186
SIDE HANDRAIL-RIGHT/LEFT HAND-900 LINE	206165	206165	206165	206165
SUPPORT FOR "BRIDGE" SYSTEM 1000 MM	206138	206138	206138	206138
SUPPORT FOR "BRIDGE" SYSTEM 1200 MM	206139	206139	206139	206139
SUPPORT FOR "BRIDGE" SYSTEM 1400 MM	206140	206140	206140	206140
SUPPORT FOR "BRIDGE" SYSTEM 1600 MM	206141	206141	206141	206141
SUPPORT FOR "BRIDGE" SYSTEM 400 MM	206154		206154	
SUPPORT FOR "BRIDGE" SYSTEM 800 MM	206137	206137	206137	206137
WATER COLUMN EXTENSION FOR 900 LINE	206290	206290	206290	206290
WATER COLUMN WITH SWIVEL ARM	206289	206289	206289	206289



ISO 14001



www.zanussiprofessional.com